



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
-----------------	-------------	----------------------	---------------------	------------------

09/880,600

06/12/2001

Lawrence G. Roberts

60010-0012

5973

29989

7590

12/30/2004

HICKMAN PALERMO TRUONG & BECKER, LLP
2055 GATEWAY PLACE
SUITE 550
SAN JOSE, CA 95110

EXAMINER

NG, CHRISTINE Y

ART UNIT

PAPER NUMBER

2663

DATE MAILED: 12/30/2004

Please find below and/or attached an Office communication concerning this application or proceeding.

Office Action Summary

Application No.

09/880,600

Applicant(s)

ROBERTS, LAWRENCE G.

Examiner

Christine Ng

Art Unit

2663

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 12 June 2001.
- 2a) ☐ This action is FINAL. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-136 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-22, 24, 27-34, 36, 39-58, 60, 63-70, 72, 75-85, 87-91, 93-97, 99-103, 105, 107-112, 114, 116, 119-121, 123-128, 130, 132, 135 and 136 is/are rejected.
- 7) ☒ Claim(s) 23, 25, 26, 35, 37, 38, 59, 61, 62, 71, 73, 74, 86, 92, 98, 104, 106, 113, 115, 117, 118, 122, 129, 131, 133 and 134 is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 12 June 2001 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
- ☐ Certified copies of the priority documents have been received.
 - ☐ Certified copies of the priority documents have been received in Application No. _____.
 - ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- ☒ Notice of References Cited (PTO-892)
- ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
- ☐ Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
Paper No(s)/Mail Date _____
- ☐ Interview Summary (PTO-413)
Paper No(s)/Mail Date _____
- ☐ Notice of Informal Patent Application (PTO-152)
- ☐ Other: _____

DETAILED ACTION

Claim Rejections - 35 USC § 112

1. The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

2. Claim 16 is rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.

Claim 16 recites the limitation "said destination" in line 5. There is insufficient antecedent basis for this limitation in the claim.

Claim Rejections - 35 USC § 102

3. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

4. Claims 1-6, 8, 10-18, 20-22, 24, 27-29, 31, 33, 34, 36, 39-41, 43, 45-53, 55-58, 60, 63-65, 67-70, 72, 75-77, 79-84, 87-90, 93-96, 99-102, 105, 107-112, 114, 116, 119-121, 123-128, 130, 132, 135 and 136 are rejected under 35 U.S.C. 102(e) as being anticipated by U.S. Patent No. 6,272,107 to Rochberger et al.

Referring to claims 1, 11, 81 and 87, Rochberger et al disclose in Figure 22 a method for recovering from a failure, comprising:

Sending a first set of information (data 380) from an ingress module (source node) to an egress module (destination node) via a first route (transit nodes #1,#2). Refer to Column 18, lines 19-21.

Detecting a failure (break 384) in said first route (transit nodes #1,#2). Refer to Column 18, lines 19-21.

In response to said failure (break 384), directing a message (restore_loopback 386) to said ingress module (source node) informing said ingress module (source node) of said failure (break 384). Refer to Column 18, lines 21-24.

In response to said message (restore_loopback 386), sending a future set of information (data 402) from said ingress module (source node) to said egress module (destination node) via an alternate route (transit node #3,#4). Refer to Column 18, lines 24-37.

Referring to claims 2, 14 and 49, Rochberger et al disclose in Figure 22 that in response to said message (restore_loopback 386), preventing other sets of information from being sent from said ingress module (source node) to said egress module (destination node) via said first route (transit nodes #1,#2). In response to the restore_loopback 386 signal, "the end nodes begin storing the incoming cells in the buffer and they stop transmitting cells onto the broken path" (Column 18, lines 24-26).

Referring to claims 3, 16 and 51, Rochberger et al disclose in Figure 22 that the said first set of information (data 380) comprises a data portion, and wherein in response to said message (restore_loopback 386), resending at least said data portion of said first set of information (data 380) from said ingress module (source node) to said

egress module (destination node) via said alternate route (transit nodes #3,#4). The cells looped back from the broken path in response to the restore_loopback 386 signal are sent to the destination over the redundant path instead. Refer to Column 18, lines 24-28.

Referring to claims 4 and 17, Rochberger et al disclose that said message (restore_loopback 386) comprises said data portion (data 380) such that said data portion (data 380) is returned to said ingress module (source node). Refer to Column 17, lines 53-56 and Column 18, lines 21-26.

Referring to claims 5, 18, 53, 84, 90, 96 and 102, Rochberger et al disclose in Figure 22 that directing said message (restore_loopback 386) to said ingress module (source node) comprises:

Identifying said ingress module (source node).

Determining a return route (VPI/VCI) to said ingress module (source node). "The end nodes know which paths are involved as they receive the restore_loopback cell over a particular VPI/VCI" (Column 16, lines 62-64).

Sending said message (restore_loopback 386) to said ingress module (source node) via said return route (VPI/VCI). Refer to Column 16, lines 62-65.

Referring to claim 6, Rochberger et al disclose in Figure 22 that determining a return route (VPI/VCI) to said source (source node) comprises identifying said source (source node). Refer to Column 16, lines 62-65.

Referring to claim 8, refer to the rejection of claims 3 and 4.

Referring to claim 10, Rochberger et al disclose that the method is implemented within a router of said network. The router is formed by the source node, transit nodes #1,#2,#3,#4 and the destination node. Refer to Column 10, lines 2-11.

Referring to claims 12 and 47, Rochberger et al disclose in Figure 5 that said first route (transits node #1,#2) and said alternate route (transits node #3,#4) are predetermined and stored within a routing table (switching table). Refer to Column 10, lines 47-59 and Column 18, lines 51-57.

Referring to claims 13 and 48, Rochberger et al disclose in Figure 5 that sending said future set of information (data 380) comprises selecting said alternate route (transit nodes #3,#4) from said routing table (switching table). Refer to Column 10, lines 47-59 and Column 18, lines 51-57.

Referring to claims 15 and 50, Rochberger et al disclose in Figure 5 that said first route (transit node #1,#2) and said alternate route (transit node #3,#4) are predetermined and stored within a routing table (switching table), and wherein preventing comprises, replacing said first route (transit nodes #1,#2) with said alternate route (transit nodes #3,#4) in said routing table (switching table). Previous redundant paths in the switching table are marked as active. Refer to Column 10, lines 47-59 and Column 18, lines 51-57.

Referring to claim 20, Rochberger et al disclose in Figure 18 that said ingress module (source node) comprises an ingress line card (port interface 320), and said egress module (destination node) comprises an egress line card (port interface 320). Refer to Column 16, lines 38-44.

Referring to claims 21 and 33, Rochberger et al disclose in Figure 22 a method, implemented within a router of a network, for recovering from a failure, comprising:

Sending a first set of information (data 380) from an ingress module (source node) to a first egress module (transit node #1) for forwarding by said first egress module (transit node #1) to a destination (destination user) external to said router.

Detecting a failure of [claim 21] said first egress module (transit node #1) or [claim 33] beyond said first egress module (transit node #1). The failure can occur in a transit node or a line (break 384) after the transit node. Refer to Column 15, lines 55-56.

In response to said failure of said first egress module (transit node #1), directing a message (restore_loopback 386) to said ingress module (source node) informing said ingress module (source node) of said first egress module failure (transit node #1). Refer to Column 18, lines 19-21.

In response to said message (restore_loopback 386), selecting an alternate egress module (transit node #3) capable of forwarding information to said destination (destination user). Refer to Column 18, lines 21-37 and lines 51-57.

Sending a future set of information (data 402) from said ingress module (source node) to said alternate egress module (transit node #3) for forwarding to said destination (destination user). Refer to Column 18, lines 21-37 and lines 51-57.

Referring to claims 22 and 34, Rochberger et al disclose in Figure 22 that the said first set of information (data 380) and said future set of information (data 402) are both part of a flow, and wherein said method further comprises: in response to said message (restore_loopback 386), preventing other sets of information associated with

said flow from being sent from said ingress module (source node) to said first egress module (transit node #1). Refer to Column 18, lines 19-37.

Referring to claims 24 and 36, Rochberger et al disclose in Figure 22 that said first set of information (data 380) and said future set of information (data 402) are both part of a flow, and wherein said method further comprises: in response to said message (restore_loopback 386), causing other sets of information associated with said flow to be sent from said ingress module (source node) to said alternate egress module (transit node #3). Refer to Column 18, lines 19-37.

Referring to claims 27 and 39, Rochberger et al disclose in Figure 22 that said first set of information (data 380) comprises a data portion, and wherein said method further comprises: in response to said message (restore_loopback 386), resending at least said data portion of said first set of information (data 380) from said ingress module (source node) to said alternate egress module (transit node #3) for forwarding to said destination (destination user). The cells looped back from the broken path in response to the restore_loopback 386 signal are sent to the destination over the redundant path instead. Refer to Column 18, lines 24-28.

Referring to claims 28 and 40, Rochberger et al disclose in Figure 22 that said message (restore_loopback 386) comprises said data portion such that said data portion is returned to said ingress module (source node). The restore_loopback 386 signal with data is returned to the source node. Refer to Column 17, lines 53-56 and Column 18, lines 21-26.

Referring to claims 29 and 41, refer to the rejection of claims 5, 18, 53, 84, 90, 96 and 102.

Referring to claims 31 and 43, Rochberger et al disclose in Figure 18 that said ingress module (source node) comprises an ingress line card (port interface 320) and in Figure 17 said first egress module (transit node #1) comprises an first egress line card (input port 316), and said alternate egress module (transit node #3) comprises a second egress line card (input port 316). Refer to Column 16, lines 21-44.

Referring to claim 45, Rochberger et al disclose in Figure 22 that the said external failure (break 384) precludes said first egress module (transit node #1) from forwarding said first set of information (data 380) to said destination (destination user). Refer to Column 16, lines 18-20.

Referring to claim 46, Rochberger et al disclose in Figure 22 a router comprising:

An ingress module (source node).

An egress module (destination node).

A forwarding mechanism (transit nodes #1,#2,#3,#4) for forwarding information between said ingress module (source node) and said egress module (destination node).

Wherein said ingress module (source node) sends a first set of information (data 380) to said forwarding mechanism (transit nodes #1,#2,#3,#4) to be forwarded to said egress module (destination node) via a first route (transit nodes #1,#2), said forwarding mechanism (transit nodes #1,#2,#3,#4) detecting a failure (break 384) in said first route (transit nodes #1,#2), and in response to said failure (break 384), said forwarding mechanism (transit node #1,#2,#3,#4) directing a message (restore_loopback 386) to

Art Unit: 2663

said ingress module (source node) informing said ingress module (source node) of said failure (break 384), and in response to said message (restore_loopback 386), said ingress module (source node) sending a future set of information (data 402) to said forwarding mechanism (transit nodes #1,#2,#3,#4) to be forwarded to said egress module (destination node) via an alternate route (transit nodes #3,#4). Refer to the rejection of claims 1, 11, 81 and 87.

Referring to claim 52, Rochberger et al disclose in Figure 22 that the said forwarding mechanism (transit nodes #1,#2,#3,#4) includes said data portion (data 380) in said message (restore_loopback) such that said data portion (data 380) is returned by said forwarding mechanism (transit nodes #1,#2,#3,#4) to said ingress module (source node). The cells looped back from the broken path in response to the restore_loopback 386 signal are sent to the destination over the redundant path instead. Refer to Column 18, lines 24-28.

Referring to claim 55, Rochberger et al disclose in Figure 18 that the ingress module (source node) comprises an ingress line card (port interface 320) and said egress module (destination node) comprises an egress line card (port interface 320) and in Figure 17 that said forwarding mechanism (transit node #1,#2,#3,#4) comprises a switching fabric (switching fabric 312). Refer to Column 10, lines 2-11 and Column 16, lines 21-44.

Referring to claim 56, Rochberger et al disclose in Figure 18 that the switching fabric (switching fabric 312) comprises a fabric card. The switching fabric performs

switching of cells from the primary to the alternative route. Refer to Column 10, lines 2-11 and Column 16, lines 21-44.

Referring to claim 57, Rochberger et al disclose in Figure 22 a router, comprising:

An ingress module (source node).

A first egress module (transit node #1).

An alternate egress module (transit node #3).

A forwarding mechanism (PNNI links between transit nodes #1,#2,#3,#4) for forwarding information between said ingress module (source node), said first egress module (transit node #1), and said alternate egress module (transit node #3).

Wherein said ingress module (source node) sends a first set of information (data 380) to said forwarding mechanism (PNNI links between transit nodes #1,#2,#3,#4) to be forwarded to said first egress module (transit node #1), said first set of information (data 380) intended to be forwarded by first egress module (transit node #1) to a destination (destination user) external to said router, said forwarding mechanism (PNNI links between transit nodes #1,#2,#3,#4) detecting a failure (transit node #1 failure) which precludes forwarding of said first set of information (data 380) to said first egress module (transit node #1), and in response to said failure (transit node #1 failure), said forwarding mechanism (PNNI links between transit nodes #1,#2,#3,#4) directing a message (restore_loopback 386) to said ingress module (source node) informing said ingress module (source node) of said failure (transit node #1 failure), and based upon said message (restore_loopback 386), said ingress module (source node) determining

Art Unit: 2663

that said first egress module (transit node #1) has failed, and in response to said message (restore_loopback 386), said ingress module (source node) selecting said alternate egress module (transit node #3) and sending a future set of information (data 402) to said forwarding mechanism (PNNI links between transit nodes #1,#2,#3,#4) to be forwarded to said alternate egress module (transit node #3), said future set of information (data 402) intended to be forwarded by said alternate egress module (transit node #3 or #4) to said destination (destination user). PNNI and Q.SAAL signaling can be used to support failure detection and alternate routing when a failure occurs. Refer to the rejection of claims 21 and 33; Column 2, lines 12-28; Column 4, lines 28-37 and Column 12, lines 44-48.

Referring to claims 58 and 70, Rochberger et al disclose in Figure 22 that said first set of information (data 380) and said future set of information (data 402) are both part of a flow, and wherein said ingress module (source node), in response to said message (restore_loopback 386), prevents other sets of information associated with said flow from being sent from said ingress module (source node) to said first egress module (transit node #1). Refer to Column 18, lines 19-37 and lines 51-57.

Referring to claims 60 and 72, Rochberger et al disclose in Figure 22 that said first set of information (data 380) and said future set of information (data 402) are both part of a flow, and wherein said ingress module (source node) in response to said message (restore_loopback 386) causes said other said sets of information associate with said flow to be sent from said ingress module (source node) to said alternate

egress module (transit node #3) via said forwarding mechanism. Refer to Column 18, lines 19-37 and lines 51-57.

Referring to claims 63 and 75, Rochberger et al disclose in Figure 22 that the first set of information comprises a data portion, and wherein said ingress module (source node), in response to said message (restore_loopback 386), resends at least said data portion of said first set of information (data 380) to said forwarding mechanism (PNNI links between transit nodes #1,#2,#3,#4) to be forwarded to said alternate egress module (transit node #3) for forwarding to destination (destination user). The cells looped back from the broken path in response to the restore_loopback 386 signal are sent to the destination over the redundant path instead. Refer to Column 18, lines 24-28.

Referring to claims 64 and 76, Rochberger et al disclose in Figure 22 that said forwarding mechanism (PNNI links between transit nodes #1,#2,#3,#4) includes said data portion in said message (restore_loopback 386) such that said data portion is returned by said forwarding mechanism (PNNI links between transit nodes #1,#2,#3,#4) to said ingress module (source node). The cells looped back from the broken path in response to the restore_loopback 386 signal are sent to the destination over the redundant path instead. Refer to Column 17, lines 53-56 Column 18, lines 19-37.

Referring to claims 65 and 77, refer to the rejection of claims 5, 18, 53, 84, 90, 96 and 102.

Referring to claims 67 and 79, refer to the rejection of claim 55.

Referring to claims 68 and 80, refer to the rejection of claim 56.

Referring to claim 69, Rochberger et al disclose in Figure 22 a router, comprising:

An ingress module (source node).

A first egress module (transit node #1).

An alternate egress module (transit node #3).

A forwarding mechanism (PNNI links between transit nodes #1,#2,#3,#4) for forwarding information between said ingress module (source node), said first egress module (transit node #1), and said alternate egress module (transit node #3).

Wherein said ingress module (source node) sends a first set of information (data 380) to said forwarding mechanism (PNNI links between transit nodes #1,#2,#3,#4) to be forwarded to said first egress module (transit node #1), said first set of information (data 380) intended to be forwarded by first egress module (transit node #1) to a destination (destination user) external to said router, said first egress module (transit node #1) detecting a failure (transit node #1 failure) which precludes forwarding of said first set of information (data 380) to said first egress module (transit node #1), and in response to said failure (transit node #1 failure), said forwarding mechanism (PNNI links between transit nodes #1,#2,#3,#4) directing a message (restore_loopback 386) to said ingress module (source node) informing said ingress module (source node) of said failure (transit node #1 failure), and based upon said message (restore_loopback 386), said ingress module (source node) determining that said first egress module (transit node #1) has failed, and in response to said message (restore_loopback 386), said ingress module (source node) selecting said alternate egress module (transit node #3)

and sending a future set of information (data 402) to said forwarding mechanism (PNNI links between transit nodes #1,#2,#3,#4) to be forwarded to said alternate egress module (transit node #3), said future set of information (data 402) intended to be forwarded by said alternate egress module (transit node #3) to said destination (destination user). The failure is detected by hardware in transit node #1. Refer to the rejection of claims 21 and 33; Column 2, lines 12-28; Column 12, lines 44-48.

Referring to claim 82, Rochberger et al disclose in Figure 22 that the said set of information (data 380) comprises a data portion, and wherein directing said message (restore_loopback 386) to said ingress module (source node) comprises returning said data portion to said ingress module (source node). Refer to Column 18, lines 19-28.

Referring to claims 83, 89, 95 and 101, Rochberger et al disclose in Figure 22 that the said set of information (data 380) comprises a data portion and wherein directing said message (restore_loopback 386) to said ingress module (source node) comprises including said data portion in said message (restore_loopback 386) such that said data portion is returned to said ingress module (source node). Data is sent back with the restore_loopback signal 386. Refer to Column 18, lines 19-28.

Referring to claims 88, 94 and 100, Rochberger et al disclose in Figure 22 that said first set of information (data 380) comprises a data portion, and wherein the mechanism for directing said message (restore_loopback 386) to said ingress module (source node) comprises a mechanism for returning said data portion (data 380) to said ingress module (source node). Refer to Column 18, lines 19-28.

Referring to claims 93 and 99, Rochberger et al disclose in Figure 22 a method comprising:

Receiving a set of information (data 380) sent by an ingress module (source node) intended to be forwarded by said egress module (destination node) to a destination (destination user) external to the router.

Detecting a failure (break 384) external to the router which precludes said egress module (destination node) from forwarding said set of information (data 380) to said destination (destination user).

In response to said failure (break 384), directing a message (restore_loopback 386) to said ingress module (source node) informing said ingress module (source node) of said failure (break 384). Refer to the rejection of claims 1, 11, 81 and 87.

Referring to claims 105 and 121, Rochberger et al disclose in Figure 22 an ingress module in a router, comprising:

Sending a first set of information (data 380) to an egress module (destination node) via a first route (transit nodes #1,#2), said first set of information (data 380) intended to be forwarded by the egress module (destination node) to a destination (destination user) external to the router.

Receiving a message (restore_loopback 386, restore_flush 390,398) indicating that said first set of information (data 380) did not reach the destination (destination user) successfully. Refer to Column 18, lines 21-28.

Determining based upon said message (restore_loopback 386, restore_flush 390,398) whether future sets of information (data 402) should be sent to the egress

module (destination node). Data 402 can be sent to the destination node once restore_flush 398 is returned to the source node. Refer to Column 18, lines 29-34.

In response to a determination that future sets of information (data 402) should be sent to the egress module (destination node), sending a future set of information (data 402) to the egress module (destination node) via an alternate route (transmit nodes #3,#4). Refer to Column 18, lines 34-37.

Referring to claims 107 and 123, Rochberger et al disclose in Figure 5 that said first route (transit nodes #1,#2) and said alternate route (transit nodes #3,#4) are predetermined and stored within a routing table (switching table), and wherein sending said future set of information (data 402) to the egress module (destination node) comprises selecting said alternate route (transit nodes #3,#4) from said routing table (switching table). Refer to Column 10, lines 47-59 and Column 18, lines 51-57.

Referring to claim 108 and 124, Rochberger et al disclose in Figure 5 that in response to a determination that future sets of information (data 402) should be sent to the egress module (destination node), preventing said future sets of information (data 402) from being sent to the egress module (destination node) via said first route (transit nodes #1,#2). The alternate paths are marked as active in the end nodes' switching tables. Refer to Column 10, lines 47-59 and Column 18, lines 51-57.

Referring to claim 109 and 125, Rochberger et al disclose in Figure 5 that said first route (transit nodes #1,#2) and said alternate route (transits node #3,#4) are predetermined and stored within a routing table (switching table), and wherein preventing comprises replacing said first route (transit nodes #1,#2) with said alternate

route (transits node #3,#4) in said routing table (switching table). Refer to Column 10, lines 47-59 and Column 18, lines 51-57.

Referring to claims 110 and 126, Rochberger et al disclose in Figure 22 that said first set of information (data 380) comprises a data portion, and wherein in response to a determination that future sets of information (data 402) should be sent to the egress module (destination node), resending at least said data portion of said first set of information (data 380) to the egress module (destination node) via said alternate route (transit nodes #3,#4). The cells looped back from the broken path in response to the restore_loopback 386 signal are sent to the destination over the redundant path instead. Refer to Column 18, lines 24-28.

Referring to claims 111 and 127, Rochberger et al disclose in Figure * that said message (restore_loopback 386) indicating that said first set of information (data 380) did not reach the destination (destination user) successfully comprises said data portion (data 380) of said first set of information. The cells looped back from the broken path in response to the restore_loopback 386 signal are sent to the destination over the redundant path instead. Refer to Column 17, lines 53-56 and Column 18, lines 21-26.

Referring to claims 112 and 128, Rochberger et al disclose in Figure 22 an ingress module in a router comprising:

Sending a first set of information (data 380) to a first egress module (transit node #1), said first set of information (data 380) intended to be forwarded by the first egress module (transit node #1) to a destination (destination user) external to the router.

Receiving a message (restore_loopback 386, restore_flush 390,398) indicating that said first set of information (data 380) did not reach the destination (destination user) successfully. Refer to Column 18, lines 21-28.

Determining based upon said message (restore_loopback 386, restore_flush 390,398) whether future sets of information (data 402) should be sent to the first egress module (transit node #1 or #2). Data 402 can be sent to the destination node once restore_flush 398 is returned to the source node. Refer to Column 18, lines 29-34.

Selecting, in response to a determination that future sets of information should not be sent to the first egress module (transit node #1), an alternate egress module (transit node #3) capable of forwarding information (data 380) to the destination (destination user). Refer to Column 18, lines 34-37.

Sending a future set of information (data 402) to the alternate aggress module (transit node #3 or #4) to be forward by the alternate egress module (transit node #3 or #4) to the destination (destination user). Refer to Column 18, lines 34-37.

Referring to claims 114 and 130, Rochberger et al disclose in Figure 22 that the first set of information (data 380) and said future set of information (data 402) are both part of a flow, and wherein in response to a determination that future sets of information should not be sent to the first egress module (transit node #1), preventing others sets of information associated with said flow from being sent to the first egress module (transit node #1). Refer to Column 18, lines 19-37.

Referring to claims 116 and 132, Rochberger et al disclose in Figure 22 that the said first set of information (data 380) and said future set of information (data 402) are

both part of a flow, and wherein in response to a determination that future sets of information should not be sent to the first egress module (transit node #1), causing other sets of information associated with said flow to be sent to the alternate egress module (transit node #3). Refer to Column 18, lines 19-37.

Referring to claims 119 and 135, Rochberger et al disclose in Figure 22 that the first set of information (data 380) comprises a data portion, and wherein said method further comprises: in response to a determination that future sets of information should not be sent to the first egress module (transit node #1), resending at least said data portion of said first set of information (data 380) to the alternate egress module (transit node #1) to be forwarded by the alternate egress module (transit node #3) to the destination (destination user). The cells looped back from the broken path in response to the restore_loopback 386 signal are sent to the destination over the redundant path instead. Refer to Column 18, lines 24-28.

Referring to claims 120 and 136, Rochberger et al disclose in Figure 22 that said message (restore_loopback 386) indicating that said first set of information (data 380) did not reach the destination successfully comprise said data portion of said first set of information (data 380). Data is sent back with the restore_loopback signal 386 to the source node. Refer to Column 18, lines 19-28.

Claim Rejections - 35 USC § 103

5. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the

Art Unit: 2663

invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

6. Claims 7, 19, 30, 42, 54, 66, 78, 85, 91, 97 and 103 are rejected under 35 U.S.C. 103(a) as being unpatentable over U.S. Patent No. 6,272,107 to Rochberger et al in view of U.S. Patent No. 6,167,025 to Hsing et al.

Rochberger et al do not disclose that identifying said ingress module comprises extracting from said first set of information an identifier which identifies said ingress module.

Hsing et al disclose in Figure 18B a re-route setup message 1802 that includes a source switch identifier which identifies the source switch. The system utilizes the source switch identifier to identify the source switch to which to send a crank-back message so the source switch can find an alternate route for the message. Refer to Column 15, lines 6-20 and Column 24, lines 1-60. Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to include that identifying said ingress module comprises extracting from said first set of information an identifier which identifies said ingress module, the motivation being so that the system can recognize the source switch and send the data back to the switch to be sent on to a different route.

7. Claims 9, 32 and 44 are rejected under 35 U.S.C. 103(a) as being unpatentable over U.S. Patent No. 6,272,107 to Rochberger et al in view of U.S. Patent No. 6,560,654 to Fedyk et al.

Rochberger et al do not disclose that the method is implemented on a routing layer of a network.

Fedyk et al disclose that the routing is performed on layer three, or the routing layer, of the network. Layer three provides switching the routing technologies for transmitting data from node to node, and provides functions such as routing and forwarding. Refer to Column 1, lines 15-33. Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to include that that the method is implemented on a routing layer of a network, the motivation being that layer three provides routing functions for data transmission among nodes of a network.

Allowable Subject Matter

8. Claims 23, 25, 26, 35, 37, 38, 59, 61, 62, 71, 73, 74, 86, 92, 98, 104, 106, 113, 115, 117, 118, 122, 129, 131, 133 and 134 are objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.

Conclusion

9. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Christine Ng whose telephone number is (571) 272-3124. The examiner can normally be reached on M-F; 8:00 am - 5:00 pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Chau Nguyen can be reached on (571) 272-3126. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Art Unit: 2663

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

C. Ng CW
December 15, 2004



CHAU NGUYEN
SUPERVISORY PATENT EXAMINER
TECHNOLOGY CENTER 2600